(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 12 January 2006 (12.01.2006)

(10) International Publication Number WO 2006/004256 Al

(51) International Patent Classification⁷: HOIS 5/18

(21) International Application Number:

PCT/KR2005/000847

(22) International Filing Date: 23 March 2005 (23.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 10-2004-0020485 25 March 2004 (25.03.2004) KI

(71) Applicant (for all designated States except US): POSTECH FOUNDATION [KR/KR]; San 31, Hyoja-dong, Nam-gu, Pohang-shi, Kyungsangbuk-do 790-784 (KR).


(72) Inventors; and

(75) Inventors/Applicants (for US only): KWON, O'Dae [KR/KR]; Department of electronic and electrical engineerin, g, POSTECH, San 31, Hyoja-dong, Nam-gu, Pohang-shi, Kyungsangbuk-do 790-784 (KR). BAE, Joongwoo [KR/KR]; Military Apt. 139-104, Namseon-ri, Namseon-myeon, Gyeryong-si, Chungcheongnam-do 320-754 (KR). AN, Sung-Jae [KR/KR]; 331-2 Yeonsan 1-dong, Yeonje-gu, Busan 611-814 (KR). KIM, Dongkwon [KR/KR]; 484-15 Dunchon 2-dong, Gangdong-gu, Seoul 134-822 (KR).

- (74) Agent: JANG, Seong Ku; 17th FL, KEC Building, 275-7, Yangjae-dong, Seocho-gu, Seoul 137-130 (KR).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, 1S, P, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: PHOTONIC QUANTUM RING LASER FOR LOW POWER CONSUMPTION DISPLAY DEVICE



(57) Abstract: A three-dimensional (3D) photonic quantum ring (PQR) laser for a low power consumption display, wherein the PQR laser has a sufficient small radius to adjust an inter-mode spacing (IMS) of oscillation modes discretely multi-wavelength-oscillating in an envelope wavelength range within the gain profile of a given semiconductor material of the PQR laser so that the IMS has a maximal value and the number of the oscillation modes is minimized. The POR laser exhibits multi-wavelength oscillation characteristics according to a 3D toroidal cavity structure, and is designed to exhibit a threshold current lower than those of LEDs and to have multi-wavelength modes in an envelope wavelength range of several nm to several tens of nm. The PQR laser consumes reduced power while maintaining desired color and high brightness equal to those of the LEDs, through an adjustment of the multi-wavelength oscillation characteristics and IMS of the PQR laser.

WO 2006/004256 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

with international search report